

Showmaster Go

Ruggedized Show Control and Audio Playback

medialon

BY 7THSENSE



- Multiple Timeline Show Control
- 16+ channels of Dante output
- Unlimited polyphonic playback mixing

This capable and flexible device is suited to many applications and installation types. Its ruggedized, small form factor makes it ideal for ride vehicles and parade floats, Showmaster Go combines a Pro version Medialon show controller with 16 channels of Dante network audio output.

Medialon Show Controller

Running Medialon Manager V7 show control software, this little box packs a lot of punch when it comes to controlling audio, video, lighting, animatronics, special effects, interfacing with PLCs and ride controllers, and synchronizing to multiple time sources.

Unlimited audio playback potential

Synchronized and asynchronously triggered audio playback are possible, mixed into the same Dante output channels. There is no limit to the polyphonic audio layering possible on Showmaster Go. You can have as many players as you want. Add more storage capacity beyond the built-in SSD with USB 3.0 drives or a network file server.

Available also as an audio-only device, the Showmaster Go is branded as MAS Pro Dante DS.

Connects to PLCs and ride controllers

Showmaster Go connects to PLCs via the network, simplifying show triggers and feedback to ride control, motion control, and show action equipment control systems.

Shock Resistant, Heat Resistant Hardware

The only moving part is a small cooling fan, so the shock and vibrations you'd expect on a ride vehicle or parade float are no sweat for Showmaster Go. With the optional shock mount, you can throw even rougher conditions at it!

Adaptable to the Size of Your Show

Need more audio output channels? Upgrade from 16 to 32 or 64 channels. Only need one Timeline? Downgrade to Manager V7 Lite. Customize the software licensing to the needs of your show.

Product Specifications	Showmaster Go
Media storage	256 GB NVMe M.2 SSD as standard
USB ports	3 × USB 2.0 (Type-A), 1 × USB 3.1 (Type-C)
Power connection	19 VDC, 60 watts (typical); DC power inlet clip
Ethernet	2 × 10/100/1000 base-T
Video output	4 × DisplayPort™ 1.2
Mounting options	VESA mount; rackmount tray (takes 1-3 units); anti-shock frame; Kingston Safe Lock
Dimensions (W × L × H)	145 mm × 152 mm × 44 mm (5-3/4" × 6" × 1-3/4")
Weight	1.4 kg (3 lbs)

Technical specifications are subject to change without prior notice. Please check www.medialon.com for the latest information.



(actual size)

Last updated: December 2023

7thSense Design Ltd

2 The Courtyard Shoreham Road
Upper Beeding
Steyning
West Sussex
BN44 3TN
UK

7thSense – London

The Record Hall
16-16A Baldwin's Gardens
Farringdon
London
EC1N 7RJ
UK

7thSense LLC – Orlando

4207 Vineland Road
Suite M1
Orlando
FL 32811
USA

