

# MAS Pro Dante DH

reliable multitrack audio server

medialon  
BY 7THSENSE



- State-of-the-art audio quality
- Centralized playback and control
- For live entertainment, attractions, museums and showrooms

**MAS Pro Dante DH is a professional multi-channel digital audio server for both multi-track applications and independent multi-zone audio playback.**

Synchronize and control audio playback on each of its output channels individually or in groups. The high quality Dante interface provides state-of-the-art high definition digital audio.

Synchronize the MAS Pro Dante DH to timecode with a Medialon show controller. MAS Pro Dante includes a remote control and configuration application to manage playback manually, but MAS Pro Dante's capabilities expand when controlled by a Medialon show controller.

## Dante Configurations

The **MAS PRO Dante DH** is equipped with Dante hardware and is licensed for either 64 or for 128 audio output channels. This DH model also provides a master clock on the network.

A small form factor **MAS PRO Dante DS** model, housed in the same chassis as the Showmaster Go, uses Dante software via the on-board Gigabit NIC. The DS model is licensed for either 32 or 64 channels of digital audio. Note: no master clock is available from the DS model.

For the MAS Pro Dante DS full specification, please see the Showmaster Go data sheet.

# MAS Pro Dante DH

reliable multitrack audio server

medialon  
BY 7THSENSE

Product Specifications	Medialon MAS Pro Dante DH
Media storage	512 GB NVMe M.2 SSD as standard
Power connection	110 VAC-220 VAC, 1.5-0.8 A (typical).
Power	165 W
Ethernet	2 × RJ45 10/100/1000 base-T
USB ports	2 × USB 2.0, 4 × USB 3.0, 2 × USB 3.1
Serial	1 × RS-232 DB9 male serial port
Video Output	1 × DisplayPort™ 1.2 connector 1 × HDMI connector
Dante spec	2 × RJ45 Dante Ethernet ports for seamless network redundancy. Up to 128 channels of 44.1-96 kHz / 16- or 24-bit digital audio on a Gigabit ethernet network. Maximum latency 3 ms at any sample rate. Provides Dante sync source.
LED type (Dante card)	3 × multicolour LEDs for Dante status, sync and error
Dimensions	2U rack 483 (W) × 89 (H) × 545 (D) mm (19" × 3.5" × 21.5")
Weight	18 kg (39½ lbs)

Technical specifications are subject to change without prior notice. Please check [www.medialon.com](http://www.medialon.com) for the latest information.

MAS Pro Dante DH  
rear panel



Last updated: June 2022